Subject Index for
Heat Transfer—Japanese Research, Volume 23, 1994

Absorptance: 2: 103–115
Ammonia/water mixture: 7: 627–644
Analyses: 6: 555–574
Analytical model: 5: 456–472
Axial concentration profile: 2: 128–140
Axisymmetric problem: 6: 498–512

Binary gas mixture: 3: 243–257
Binary mixture: 2: 128–140
Blade wheel: 5: 440–455
Boiler: 4: 349–363
Boiling: 1: 52–65; 2: 128–140; 5: 415–426
Boundary condition: 3: 258–276
Boundary element method: 6: 498–512
Buoyant plume: 1: 86–101

Carbon–carbon composite: 6: 555–574
Casting machine: 1: 35–51
Cell model: 3: 258–276
Ceramic coating: 2: 166–184
Circular tube: 8: 739–755
Close-contact melting: 2: 198–213; 4: 364–380
Cold heat storage: 3: 292–312
Composite foam: 3: 258–276
Computational mechanics: 6: 498–512
Condensate pattern: 4: 330–348
Condensation coefficient: 7: 595–610
Condensation: 4: 330–348; 7: 595–610; 627–644
Continuous casting: 1: 35–51
Continuous phase: 3: 258–276
Control: 4: 349–363
Convection: 4: 364–380
Cooling of electronic equipment: 2: 116–127
Correlation: 6: 485–497
Countercurrent flow limitation: 4: 313–329; 7: 611–626
Critical heat flux: 5: 415–426; 7: 611–626; 8: 739–755
Cryogenics: 4: 381–398; 399–414

Cylinder banks: 2: 153–165
Cylinders: 7: 645–657
Cylindrical capsule: 2: 198–213

Density inversion of water: 7: 645–657
Detection method: 5: 456–472
Disk MHD generator: 3: 230–242
Dispersed phase: 3: 258–276
Dream pipe: 6: 525–543

Eccentricity: 5: 427–439
Eddy current: 6: 555–574
Effect of fin: 1: 17–34
Effective thermal conductivity: 1: 66–85
Electrochemical technique: 7: 658–673
Electromagnetic ultrasonic technique: 6: 555–574
Emissivity: 3: 277–291
Energy storage: 1: 1–16; 17–34
Ethanol and water: 4: 330–348
Evaporation: 2: 128–140; 166–184; 7: 595–610
Experiment: 2: 141–152; 4: 330–348; 7: 627–644
Extended heat-transfer surface: 6: 513–524

Film thickness: 6: 485–497
Fin: 8: 756–768
Finite-element method: 7: 575–594; 8: 675–692
Flash evaporation: 6: 544–555
Flooding: 4: 313–329
Fluidized bed: 4: 349–363
Forced convection: 2: 141–152; 3: 213–229; 5: 415–426; 440–455; 6: 525–543; 8: 675–692
Forced-convection heat transfer: 1: 66–85
Fourier series: 4: 364–380
Free convection: 7: 627–644
Functionally gradient material: 8: 710–726

Geothermal heat transfer: 7: 658–673
Gravity-controlled condensation: 4: 330–348
Grid: 8: 756–768

Harmonic function: 6: 498–512
Heat conduction: 1: 35–51; 6: 498–512; 7: 575–594; 8: 675–692; 710–726
Heat exchanger: 2: 153–165; 185–197; 3: 213–229
Heat-flux distribution: 1: 1–16; 17–34
Heat pipe: 1: 52–65; 2: 128–140; 4: 313–329
Heat pipes: 7: 611–626
Heat sink: 3: 213–229
Heat transfer: 1: 86–101; 2: 103–115; 116–127; 141–152; 153–165; 166–184; 185–197; 3: 213–229; 230–242; 277–291; 4: 330–348; 364–380; 381–398; 399–414; 6: 513–524; 525–543; 7: 575–594; 627–644; 8: 727–738; 756–768
Heat-transfer coefficient: 4: 349–363; 6: 544–555
Heat-transfer correlation: 1: 52–65
Heat-transfer enhancement: 5: 427–439; 440–455; 6: 513–524; 8: 756–768
Heat-transfer tube: 1: 1–16
Hemispherical reflectance: 2: 103–115
Horizontal cylinder: 1: 86–101
Horizontal plate: 6: 513–524; 8: 756–768
Horizontal rectangular duct: 6: 485–497
Horizontal tube: 7: 627–644
Horizontal type: 1: 35–51
HTGR: 3: 243–257

Induced flow rate: 2: 116–127
Induction heating: 6: 555–574
Induction motor: 2: 141–152
Information compression: 5: 473–484
Information loop: 5: 473–484
Infrared radiometer: 5: 456–472
In-line arrangement: 2: 153–165
Interaction: 1: 86–101
Internal heterogeneous space: 5: 456–472

Latent heat: 1: 1–16; 17–34; 3: 292–312
Lifetime: 2: 166–184
Lorentz force: 3: 230–242
LSI package: 8: 675–692
LWR: 5: 473–484

Magnetohydrodynamics: 3: 230–242
Mass transfer: 4: 330–348; 6: 485–497; 7: 658–673
Mass-transfer coefficient: 6: 485–497
Measurement method: 3: 277–291
Melting: 7: 645–657
Metal: 3: 277–291
MHD iteration: 3: 230–242
MHD power generation: 3: 230–242
Molecular diffusion: 3: 243–257
Multilayer insulation: 4: 381–398; 399–414
Multilayered material: 8: 710–726
Multiphase flow: 1: 52–65; 5: 415–426; 6: 485–497; 8: 727–738

Natural circulation: 3: 243–257
Natural convection: 1: 86–101; 2: 116–127; 153–165; 198–213; 5: 427–439; 6: 513–524; 8: 727–738; 756–768
Navier–Stokes equations: 8: 675–692
Neoprene foam: 3: 258–276
Nonazeotropic mixture: 7: 627–644
Nonhomogeneous porous layer: 1: 66–85
Nuclear reactor: 4: 313–329; 5: 473–484
Nuclear reactors: 7: 611–626
Numerical analysis: 2: 198–213; 3: 243–257; 5: 427–439; 6: 498–512; 7: 575–594
Numerical calculation: 1: 17–34

O/W-type emulsion: 3: 292–312
One-dimensional flow model: 2: 128–140
Oscillating flow: 6: 525–543
Oscillation modes: 8: 693–709

Packed beds: 7: 658–673
Parallel channels: 8: 693–709
Parallel plates: 2: 116–127
Parameter effects: 8: 739–755
Passive safety function: 5: 473–484
Passive safety reactor: 5: 473–484
Phase change: 1: 35–51; 2: 198–213; 4: 364–380
Phase transition: 7: 595–610

Pin fin: 3: 213–229
Pipe flow: 5: 415–426; 440–455
Porous materials: 3: 258–276
Pressure drop: 2: 185–197; 5: 440–455
Pressure loss: 3: 213–229
Promoter: 2: 185–197

Radial duct: 2: 141–152
Real surface: 2: 103–115
Rectangular channel: 4: 313–329; 8: 739–755
Refrigerant: 7: 627–644
Reverse U-shaped tube: 3: 243–257
Rotor: 2: 141–152

Saturated two-phase flow: 8: 739–755
Saturation temperature: 6: 544–555
Self-organization: 5: 473–484
Separated flow: 8: 739–755
Shock tube: 7: 595–610
Shock wave: 7: 595–610
Similarity curve: 1: 17–34
Similarity rule: 1: 1–16; 17–34
SIMPLE algorithm: 8: 675–692
Simulation: 1: 35–51
Single droplet: 2: 166–184
Solidification: 1: 1–16; 17–34; 35–51; 7: 645–657
Solid/liquid phase-change heat transfer: 7: 645–657
Specific heat: 3: 277–291
Spectroscopic measurement: 2: 103–115
Spherical particle layer: 1: 66–85
Squeezing force: 4: 364–380
Standby safety system: 5: 473–484
Static mixer: 2: 185–197
Steady flow: 8: 675–692
Steady melting: 4: 364–380
Steel: 1: 35–51
Stepwise heating: 8: 710–726
Sticking probability: 7: 595–610
Straight fin: 1: 1–16; 17–34
Supercooling: 3: 292–312
Surface roughness: 2: 103–115
Surface tension: 8: 727–738
Swirl flow: 2: 185–197; 5: 440–455
Synergetics: 5: 473–484
Syntactic foam: 3: 258–276

Temperature distribution: 1: 1–16; 17–34
Temperature field: 5: 456–472
Temperature response: 8: 710–726
Thermal boundary layer: 1: 66–85
Thermal conduction: 4: 381–398
Thermal conductivity: 1: 1–16; 3: 258–276
Thermal diffusion: 6: 525–543
Thermal diffusivity: 6: 555–574
Thermal-energy storage: 2: 198–213; 7: 645–657
Thermal insulation: 4: 381–398; 399–414
Thermal performance: 5: 440–455
Thermal radiation: 2: 103–115; 3: 277–291; 4: 381–398; 399–414; 7: 575–594
Thermophysical property: 2: 103–115; 3: 277–291; 292–312
Thermosiphon: 1: 52–65
Thin liquid film flow: 6: 485–497
Thin liquid sublayer: 8: 739–755
Three dimensions: 7: 575–594; 8: 675–692
Tube thickness: 1: 1–16
Turbulence: 6: 485–497
Turbulent flow: 2: 141–152; 185–197
Twisted tape: 2: 185–197
Two-phase flow instability: 8: 693–709
Type 304 stainless steel: 6: 555–574

Upward flow: 8: 739–755

Vacuum: 6: 544–555
Vapor blanket: 8: 739–755
Vertical array: 1: 86–101
Vertical channel: 8: 739–755
Vertical channels: 7: 611–626
Vertical surface: 4: 330–348
Vertical upward flow: 5: 415–426
Volume fraction: 3: 258–276

Wall temperature distribution: 2: 128–140
Working fluid: 8: 727–738

X-ray tube: 7: 575–594